

March 1, 2004  
Case No.: FR 000135 (7790/334)  
Serial No : 10/015, 843  
December 10, 2001  
Page 3 of 9

**CLAIM AMENDMENTS:**

Please cancel pending claims 1-6, and 10 as shown below without prejudice or disclaimer as to the subject matter of claims 1-10.

Please add claims 11-16 as shown below.

The following listing of claims 1-16 will replace all prior versions, and listings, of claims in the application:

1.-6. (Cancelled)

7.-9. (Withdrawn)

10. (Cancelled)

11. (New) A housing for an electronic device, comprising:

a main body with an opening;

a cover moveable relative to said main body between an assembled position for blocking said opening and a disassembled position for allowing access to said opening;

a locking element moveable between a locked position for locking said main body and said cover in the assembled position and an unlocked position for facilitating a removal of said cover from said main body in the disassembled position;

wherein, in the assembled position, said cover includes at least one hook extending through said opening into said main body; and

wherein, in the locked position, said locking element extends through and into said main body and cooperates with said at least one hook to lock said main body and said cover in the assembled position.

March 1, 2004

Case No.: FR 000135 (7790/334)

Serial No.: 10/015, 843

December 10, 2001

Page 4 of 9

12. (New) The housing of claim 11, further comprising:  
guiding means for guiding said locking element between the locked position and the unlocked position.
13. (New) The housing of claim 11, further comprising:  
retaining means for retaining said locking element in the locked position.
14. (New) A housing for an electronic device, comprising:  
a main body with an opening;  
a cover moveable relative to said main body between an assembled position for blocking said opening and a disassembled position for allowing access to said opening;  
a locking element moveable between a locked position for locking said main body and said cover in the assembled position and an unlocked position for facilitating a removal of said cover from said main body in the disassembled position;  
wherein, in the assembled position, said main body includes at least one hook extending through said opening into said cover; and  
wherein, in the locked position, said locking element extends through and into said cover and cooperates with said at least one hook to lock said main body and said cover in the assembled position.
15. (New) The housing of claim 14, further comprising:  
guiding means for guiding said locking element between the locked position and the unlocked position.
16. (New) The housing of claim 14, further comprising:  
retaining means for retaining said locking element in the locked position.